

Technical Data Sheet

4M Hardener 851

Product description

4M Hardeners 851 are polyisocyanate based hardeners for 2K products. They are especially designed for 4M 2K acrylic paints, 4M MS and HS clearcoats, 4M 2K sealers. Having more kind of hardeners means that all painting conditions can be optimized and reliable application can be achieved..

Choice of Hardener

The recommendations below are for guidance only. Please refer to the TDS of the respective 2K products for more detailed information about the selection of the hardeners

4M Hardener 851	
Density:	0.92 - 0.96(g/cm ³)
Solid content:	26.00 - 30.00%
Complete respray	Unsuitable
Partial respray	Suitable
15C – 20C	Suitable
20C – 25C	Suitable
>30C	Not particularly suitable
>30C	Unsuitable

General notes

1. Seal container immediately after use.
2. Do NOT store hardeners in dump condition

Technical Data Sheet

4M Hardener 851

Health and Safety

1. For full Health and Safety information please refer to Safety Data Sheet (SDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment.

IMPORTANT NOTE:

These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application

Packaging	color	Expiry
1.150kgm - 0.575kgm	clear	1 years at 20°C

Material safety data:

When using these products it is required to comply with the national regulations for health and safety